

Warranty

- ◆ 2 years Manufacturer Warranty

Manufacturing:

- ◆ original cell sorting system ensures the best electric cell match
- ◆ EL-Testing before packing
- ◆ Comprehensive module power testing

Performance:

- ◆ Upgraded module efficiency and portability.
- ◆ Optimized performance under low light conditions.
- ◆ Reliable technology with long-term stability and lifespan.
- ◆ Equipped with MC4 output for stable power transfer and wide compatibility with portable power stations.

Mechanical Data

Standard Test Conditions AM=1.5,E=1000W/m²,TC=25°C

Nominal Power	200W
Cell Type	HPBC Mono-crystalline
Cell Efficiency	>25%
Maximum Power Current (Impp)	10.50A
Maximum Power Voltage (Vmpp)	19.05V
Open-circuit Voltage (Voc)	21.75V
Short-circuit Current (Isc)	11.13A
DC Output-1	MC4
Output Tolerance	0-3%
Working Temperature	-20~+65°C

Packaging

Module Dimensions (Folded)	580*580*40mm
Module Dimensions (Unfolded)	2190*580*10mm
Weight (net/Gross)	6.19/7.0kg
Pieces per Pallet	44 pcs
Gross Weight per Pallet	350kg
Pallet Dimensions	1200*1100*750mm



SOLMAX NEW ENERGY B.V.

Address: defensiedok 18, 3433 KL Nieuwegein, The Netherlands
 Tel: 0031-307855708
 Whatsapp: 031-620074476
 Email: info15@solarfam.nl

