

Warranty

- ◆ 2 years Manufacturer Warranty

Manufacturing:

- ◆ original cell sorting system ensures the best electric cell match
- ◆ EL-Testing before packing
- ◆ Comprehensive module power testing

Performance:

- ◆ Upgraded efficiency and unprecedented flexibility.
- ◆ Lower operating temperature and excellent thermal performance
- ◆ Reliable technology with long-term stability and lifespan
- ◆ Ideal for balconies, RVs, and BIPV applications.



SZ-200-MC

Mechanical Data

Standard Test Conditions AM=1.5, E=1000W/m², TC=25°C

Nominal Power	200W
Cell Type	Mono-crystalline
Cell Efficiency	>22.5%
Maximum Power Current (Impp)	6.64A
Maximum Power Voltage (Vmpp)	30.16V
Open-circuit Voltage (Voc)	35.36V
Short-circuit Current (Isc)	7.03A
Maximum System Voltage	200V
Output Tolerance	0~+3%
Cable (MC4)	900mm/2.5mm ²
Module Structure	CPC/ Cell / EVA/Backsheet
Junction box rating	≥IP67
Diode	√
Operating temperature range	-20°C~+65°C

Packaging

Module Dimensions	1290*790*2mm
Module Weight	4.2/6.5kg
Package	Single package
Pieces per Pallet	30 pcs
Gross Weight per Pallet	220kg
Pallet Dimensions	1200*1100*940mm

SOLMAX NEW ENERGY B.V.

Address: defensiedok 18, 3433 KL Nieuwegein, Utrecht, NL
 TEL:0031-307855708
 Whatsapp:031-620074476
 Email:info@solarfam.nl

